



2019
product catalogue
price list

VODINOX[®]
REFRIGERATION AND DISHWASHING

vodinox.com



The roots of Apaydin Industrial Ltd. date back to the foundation of Apaydin Machinery Co., that has been manufacturing automation machines, and offering spare parts and after-sales maintenance services to companies in different industries for over 30 years. We mainly specialize in the manufacture of stainless steel machines and equipment.

Our experience in stainless steel processing gave us the motivation to diversify our activities, which led us to establishing a new factory for carrying out the production of commercial kitchen equipment. Combining our engineering know-how with a new inspiration, we started manufacturing commercial refrigerators and freezers for some of the leading companies in this field with their brands as well as our own brand Vodinox.

With 30 years of experience, we carry out all activities of designing, developing, engineering and manufacturing within our own factory, and we provide project design, application, training and after-sales services for hotels, restaurants, cafes, hospitals etc. Apart from supplying our products to the local market, we export them to more than 15 countries in the world.

We consider Research and Development (R&D) practices as the driving force behind the creation of high-quality products, and we accept them as the core of our production strategies. To meet the changing and developing demands of the market, we use state-of-the-art machines throughout the production process with the help of our highly skilled and experienced technical team. Our primary goal is to produce high quality technology equipment and deliver tailor-made solutions to our customers.



1

REFRIGERATED COUNTERS
page 1-10



2

REFRIGERATED CABINETS
page 11-19



3

PREPARATION LINE
page 20-23



4

BAR LINE
page 24-26



5

DISHWASHERS
page 27-29





UGR-135

UGF-135



UGR-180

UGF-180



UGR-225

UGF-225

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
UGR-135	-2°C+8°C	1350	850/900	700	50	264	R134a	215	277	€ 1.430
							R290	218	380	€ 1.460
UGR-180	-2°C+8°C	1800	850/900	700	50	413	R134a	215	277	€ 1.700
							R290	218	280	€ 1.730
UGR-225	-2°C+8°C	2250	850/900	700	50	562	R134a	289	399	€ 2.130
							R290	198	356	€ 2.160
UGF-135	-20°C-15°C	1350	850/900	700	50	264	R404a	328	292	€ 1.850
							R290	285	313	€ 1.900
UGF-180	-20°C-15°C	1800	850/900	700	50	413	R404a	328	292	€ 2.200
							R290	285	313	€ 2.250
UGF-225	-20°C-15°C	2250	850/900	700	50	562	R404a	409	391	€ 3.150
							R290	370	420	€ 3.200

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	<p>Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 350</p>
	<p>Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 450</p>



UGR-120
UGF-120

UGR-165
UGF-165

UGR-210
UGF-210



Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
UGR-120	-2°C+8°C	1200	850/900	700	50	264	R134a	215	277	€ 1.380
							R290	218	380	€ 1.410
UGR-165	-2°C+8°C	1650	850/900	700	50	413	R134a	215	277	€ 1.650
							R290	218	280	€ 1.680
UGR-210	-2°C+8°C	2100	850/900	700	50	562	R134a	289	399	€ 2.080
							R290	198	356	€ 2.110
UGF-120	-20°C-15°C	1200	850/900	700	50	264	R404a	328	292	€ 1.800
							R290	285	313	€ 1.850
UGF-165	-20°C-15°C	1650	850/900	700	50	413	R404a	328	292	€ 2.150
							R290	285	313	€ 2.200
UGF-210	-20°C-15°C	2100	850/900	700	50	562	R404a	409	391	€ 3.100
							R290	370	420	€ 3.150

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	<p>Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 350</p>
	<p>Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 450</p>



UGR-135-GL
UGR-120-GL



UGR-180-GL
UGR-165-GL



UGR-225-GL
UGR-210-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
UGR-135-GL	-2°C+8°C	1350	850/900	700	50	264	R134a	215	277	€ 1.730
							R290	218	280	€ 1.760
UGR-180-GL	-2°C+8°C	1800	850/900	700	50	413	R134a	215	277	€ 2.150
							R290	218	280	€ 2.180
UGR-225-GL	-2°C+8°C	2250	850/900	700	50	562	R134a	289	399	€ 2.730
							R290	198	356	€ 2.760
UGR-120-GL	-2°C+8°C	1200	850/900	700	50	264	R134a	215	277	€ 1.680
							R290	218	280	€ 1.710
UGR-165-GL	-2°C+8°C	1650	850/900	700	50	413	R134a	215	277	€ 2.100
							R290	218	280	€ 2.130
UGR-210-GL	-2°C+8°C	2100	850/900	700	50	562	R134a	289	399	€ 2.680
							R290	198	356	€ 2.710

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options	Price (€)
GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



UGR-135-SN



UGR-180-SN



UGR-225-SN



Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
UGR-135-SN	-2°C+8°C	1350	850/900	700	50	264	R134a	215	277	€ 1.730
							R290	218	280	€ 1.760
UGR-180-SN	-2°C+8°C	1800	850/900	700	50	413	R134a	215	277	€ 2.150
							R290	218	280	€ 2.180
UGR-225-SN	-2°C+8°C	2250	850/900	700	50	562	R134a	289	399	€ 2.630
							R290	198	356	€ 2.660

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 1/1 Extra shelf	20
GN 1/1 Slides extra set	15
Lock Kit	40
220 V 60Hz	40
Double drawers set	350
Triple drawers set	450

	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350
	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system	€ 450



BGR-135
BGF-135

BGR-180
BGF-180

BGR-225
BGF-225

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
BGR-135	-2°C+8°C	1350	600/620	700	50	162	R134a	215	277	€ 1.540
							R290	218	280	€ 1.570
BGR-180	-2°C+8°C	1800	600/620	700	50	254	R134a	215	277	€ 1.810
							R290	218	280	€ 1.840
BGR-225	-2°C+8°C	2250	600/620	700	50	345	R134a	289	399	€ 2.170
							R290	198	356	€ 2.200
BGF-135	-20°C-15°C	1350	600/620	700	50	162	R404a	328	292	€ 2.000
							R290	285	313	€ 2.050
BGF-180	-20°C-15°C	1800	600/620	700	50	254	R404a	328	292	€ 2.350
							R290	285	313	€ 2.400
BGF-225	-20°C-15°C	2250	600/620	700	50	345	R404a	409	391	€ 2.590
							R290	370	407	€ 2.640

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel without upstand worktop
- Stainless Steel GN 1/1 slides, height adjustable
- Stainless Steel adjustable legs, from 70 to 90 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 1/1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
One drawer set	250
Double drawers set	350

	Increase of price by changing door to one drawer set, detachable telescopic SS runners, soft-closing system	€ 250
	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350



BGR-120
BGF-120

BGR-165
BGF-165

BGR-210
BGF-210

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
BGR-120	-2°C+8°C	1200	600/620	700	50	162	R134a	215	277	€ 1.500
							R290	218	280	€ 1.530
BGR-165	-2°C+8°C	1650	600/620	700	50	254	R134a	215	277	€ 1.750
							R290	218	280	€ 1.780
BGR-210	-2°C+8°C	2100	600/620	700	50	345	R134a	289	399	€ 2.150
							R290	198	356	€ 2.180
BGF-120	-20°C-15°C	1200	600/620	700	50	162	R404a	328	292	€ 1.950
							R290	285	313	€ 2.000
BGF-165	-20°C-15°C	1650	600/620	700	50	254	R404a	328	292	€ 2.150
							R290	285	313	€ 2.200
BGF-210	-20°C-15°C	2100	600/620	700	50	345	R404a	409	391	€ 2.600
							R290	370	407	€ 2.650

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel without upstand worktop
- Stainless Steel GN 1/1 slides, height adjustable
- Stainless Steel adjustable legs, from 70 to 90 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 1/1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
One drawer set	250
Double drawers set	350

	Increase of price by changing door to one drawer set, detachable telescopic SS runners, soft-closing system	€ 250
	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350



USR-150
USF-150



USR-200
USF-200



USR-250
USF-250



Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
USR-150	-2°C+8°C	1500	850/900	600	50	246	R134a	215	277	€ 1.430
							R290	218	280	€ 1.460
USR-200	-2°C+8°C	2000	850/900	600	50	383	R134a	215	277	€ 1.700
							R290	218	280	€ 1.730
USR-250	-2°C+8°C	2500	850/900	600	50	520	R134a	289	399	€ 2.130
							R290	198	356	€ 2.160
USF-150	-20°C-15°C	1500	850/900	600	50	246	R404a	328	292	€ 1.850
							R290	285	313	€ 1.900
USF-200	-20°C-15°C	2000	850/900	600	50	383	R404a	328	292	€ 2.200
							R290	285	313	€ 2.250
USF-200	-20°C-15°C	2500	850/900	600	50	520	R404a	409	391	€ 3.150
							R290	370	407	€ 3.200

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	20
Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350
	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system	€ 450



USR-130
USF-130

USR-180
USF-180

USR-230
USF-230

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
USR-130	-2°C+8°C	1300	850/900	600	50	246	R134a	215	277	€ 1.380
							R290	218	280	€ 1.410
USR-180	-2°C+8°C	1800	850/900	600	50	383	R134a	215	277	€ 1.650
							R290	218	280	€ 1.680
USR-230	-2°C+8°C	2300	850/900	600	50	520	R134a	289	399	€ 2.080
							R290	198	356	€ 2.110
USF-130	-20°C-15°C	1300	850/900	600	50	246	R404a	328	292	€ 1.800
							R290	285	313	€ 1.850
USF-180	-20°C-15°C	1800	850/900	600	50	383	R404a	328	292	€ 2.150
							R290	285	313	€ 2.200
USF-230	-20°C-15°C	2300	850/900	600	50	520	R404a	409	391	€ 3.100
							R290	370	407	€ 3.150

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	20
Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350
	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system	€ 450



USR-150-GL
USR-130-GL



USR-200-GL
USR-180-GL



USR-250-GL
USR-230-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
USR-150-GL	-2°C+8°C	1500	850/900	600	50	246	R134a	215	277	€ 1.730
							R290	218	280	€ 1.760
USR-200-GL	-2°C+8°C	2000	850/900	600	50	383	R134a	215	277	€ 2.150
							R290	218	280	€ 2.180
USR-250-GL	-2°C+8°C	2500	850/900	600	50	520	R134a	289	399	€ 2.730
							R290	198	356	€ 2.760
USR-130-GL	-2°C+8°C	1300	850/900	600	50	246	R134a	215	277	€ 1.680
							R290	285	313	€ 1.710
USR-180-GL	-2°C+8°C	1800	850/900	600	50	383	R134a	215	277	€ 2.100
							R290	285	313	€ 2.130
USR-230-GL	-2°C+8°C	2300	850/900	600	50	520	R134a	289	399	€ 2.680
							R290	370	407	€ 2.710

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options	Price (€)
Extra shelf	20
Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Without upstand worktop	30
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



USR-150-SN



USR-200-SN



USR-250-SN

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
USR-150-SN	-2°C+8°C	1500	850/900	600	50	246	R134a	215	277	€ 1.730
							R290	218	280	€ 1.760
USR-200-SN	-2°C+8°C	2000	850/900	600	50	383	R134a	215	277	€ 2.150
							R290	218	280	€ 2.180
USR-250-SN	-2°C+8°C	2500	850/900	600	50	520	R134a	289	399	€ 2.630
							R290	198	356	€ 2.660

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop, with 60 mm sanitary upstand
- Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	20
Slides extra set	15
Lock Kit	40
220 V 60Hz	40
Double drawers set	350
Triple drawers set	450

	<p>Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 350</p>
	<p>Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 450</p>



CGR-801
CGF-801



CGR-1602
CGF-1602

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CGR-801	-2°C+8°C	705	1950 / 2000	845	60	490	R134a	289	399	€ 1.550
							R290	198	356	€ 1.580
CGF-801	-20°C-15°C	705	1950 / 2000	845	60	490	R404a	409	391	€ 1.870
							R290	370	407	€ 1.920
CGR-1602	-2°C+8°C	1410	1950 / 2000	845	60	1132	R134a	471	760	€ 2.170
							R290	384	757	€ 2.200
CGF-1602	-20°C-15°C	1410	1950 / 2000	845	60	1132	R404a	680	796	€ 2.750
							R290	839	907	€ 2.800

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- GN 2/1 Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 2/1 Extra shelf	25
GN 2/1 Slides extra set	15
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CGR-811
CGF-811



CGR-1612
CGF-1612

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CGR-811	-2°C+8°C	705	2030 / 2080	845	60	490	R134a	289	399	€ 1.650
							R290	198	356	€ 1.680
CGF-811	-20°C-15°C	705	2030 / 2080	845	60	490	R404a	409	391	€ 1.970
							R290	370	407	€ 2.020
CGR-1612	-2°C+8°C	1410	2030 / 2080	845	60	1132	R134a	471	760	€ 2.290
							R290	384	757	€ 2.320
CGF-1612	-20°C-15°C	1410	2030 / 2080	845	60	1132	R404a	680	796	€ 2.870
							R290	839	907	€ 2.930

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- GN 2/1 Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 2/1 Extra shelf	25
GN 2/1 Slides extra set	15
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CGR-801-GL



CGR-811-GL



CGR-1602-GL



CGR-1612-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CGR-801-GL	-2°C+8°C	705	1950 / 2000	845	60	490	R134a	289	399	€ 1.900
							R290	198	356	€ 1.930
CGR-811-GL	-2°C+8°C	705	2030 / 2080	845	60	490	R134a	409	391	€ 2.000
							R290	198	356	€ 2.030
CGR-1602-GL	-2°C+8°C	1410	1950 / 2000	845	60	1132	R134a	471	760	€ 2.870
							R290	384	757	€ 2.900
CGR-1612-GL	-2°C+8°C	1410	2030 / 2080	845	60	1132	R134a	680	796	€ 2.990
							R290	384	757	€ 3.020

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- GN 2/1 Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 2/1 Extra shelf	25
GN 2/1 Slides extra set	15
Lock Kit	40
4 castors set	70
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CG-1602-DUAL/1



CG-1602-DUAL/2



CG-1602-MIX

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CG-1602-DUAL/1	-2°C+8°C	1410	1950 / 2000	845	60	490 x 2	R134a	289 + 289	399 + 399	€ 3.900
							R290	243 + 243	502 + 502	€ 3.980
CG-1602-DUAL/2	-20°C-15°C	1410	1950 / 2000	845	60	490 x 2	R404a	409 + 409	391 + 391	€ 4.400
							R290	491 + 491	606 + 606	€ 4.520
CG-1602-MIX	-2°C+8°C / -20°C-15°C	1410	1950 / 2000	845	60	490 x 2	R134a+R404a	289 + 409	399 + 391	€ 4.140
							R290	243 + 491	502 + 606	€ 4.240

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- GN 2/1 Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
GN 2/1 Extra shelf	25
GN 2/1 Slides extra set	15
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CSR-701
CSF-701



CSR-1402
CSF-1402

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CSR-701	-2°C+8°C	705	1950 / 2000	745	60	419	R134a	289	399	€ 1.530
							R290	198	356	€ 1.560
CSF-701	-20°C-15°C	705	1950 / 2000	745	60	419	R404a	409	391	€ 1.850
							R290	370	407	€ 1.900
CSR-1402	-2°C+8°C	1410	1950 / 2000	745	60	968	R134a	471	760	€ 2.150
							R290	384	757	€ 2.180
CSF-1402	-20°C-15°C	1410	1950 / 2000	745	60	968	R404a	680	796	€ 2.730
							R290	839	907	€ 2.780

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	25
Slides extra set	15
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CSR-711
CSF-711



CSR-1412
CSF-1412

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CSR-711	-2°C+8°C	705	2030 / 2080	745	60	419	R134a	289	399	€ 1.630
							R290	198	356	€ 1.660
CSF-711	-20°C-15°C	705	2030 / 2080	745	60	419	R404a	409	391	€ 1.950
							R290	370	407	€ 2.000
CSR-1412	-2°C+8°C	1410	2030 / 2080	745	60	968	R134a	471	760	€ 2.270
							R290	384	757	€ 2.320
CSF-1412	-20°C-15°C	1410	2030 / 2080	745	60	968	R404a	680	796	€ 2.850
							R290	839	907	€ 2.900

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	25
Slides extra set	15
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CSR-701-GL



CSR-711-GL



CSR-1402-GL



CSR-1412-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CSR-701-GL	-2°C+8°C	705	1950 / 2000	745	60	419	R134a	289	399	€ 1.880
							R290	198	356	€ 1.910
CSR-711-GL	-2°C+8°C	705	2030 / 2080	745	60	419	R134a	409	391	€ 1.980
							R290	198	356	€ 2.010
CSR-1402-GL	-2°C+8°C	1410	1950 / 2000	745	60	968	R134a	471	760	€ 2.850
							R290	384	757	€ 2.880
CSR-1412-GL	-2°C+8°C	1410	2030 / 2080	745	60	968	R134a	680	796	€ 2.970
							R290	384	757	€ 3.000

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- Shelves made of plasticized steel wire, height adjustable
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Extra shelf	25
Slides extra set	15
Lock Kit	40
4 castors set	70
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CGR-801-PK
CGF-801-PK



CGR-1602-PK
CGF-1602-PK

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CGR-801-PK	-2°C+8°C	705	1950 / 2000	845	60	490	R134a	289	399	€ 1.750
							R290	198	356	€ 1.780
CGF-801-PK	-20°C-15°C	705	1950 / 2000	845	60	490	R404a	409	391	€ 2.120
							R290	370	407	€ 2.170
CGR-1602-PK	-2°C+8°C	1410	1950 / 2000	845	60	1132	R134a	471	760	€ 2.620
							R290	384	757	€ 2.650
CGF-1602-PK	-20°C-15°C	1410	1950 / 2000	845	60	1132	R404a	680	796	€ 3.200
							R290	839	907	€ 3.250

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- 20 / 40 Tray Capacity
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Lock Kit	40
4 castors set	70
Half Door	150
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



CGR-801-PK-GL



CGR-1602-PK-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
CGR-801-PK-GL	-2°C+8°C	705	1950 / 2000	845	60	490	R134a	289	399	€ 2.100
							R290	198	356	€ 2.130
CGR-1602-PK-GL	-2°C+8°C	1410	1950 / 2000	845	60	1132	R134a	471	760	€ 3.320
							R290	384	757	€ 3.350

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Interior lighting for refrigerators
- 20 / 40 Tray Capacity
- Adjustable legs, 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient

Options

Options	Price (€)
Lock Kit	40
4 castors set	70
220 V 60Hz	40
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20



MGR-135
MGR-180

MGR-135-MR
MGR-180-MR

MGR-135-GR
MGR-180-GR



Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
MGR-135	-2°C+8°C	1350	1380/1430	700	50	264 / 7 x ¼	R134a	215	277	€ 2.150
							R290	218	280	€ 2.180
MGR-180	-2°C+8°C	1800	1380/1430	700	50	413 / 10 x ¼	R134a	215	277	€ 2.400
							R290	218	280	€ 2.430
MGR-135-MR	-2°C+8°C	1350	1380/1430	700	50	264 / 7 x ¼	R134a	215	277	€ 2.650
							R290	218	280	€ 2.680
MGR-180-MR	-2°C+8°C	1800	1380/1430	700	50	413 / 10 x ¼	R134a	215	277	€ 3.000
							R290	218	280	€ 3.030
MGR-135-GR	-2°C+8°C	1350	1380/1430	700	50	264 / 7 x ¼	R134a	215	277	€ 2.700
							R290	218	280	€ 2.730
MGR-180-GR	-2°C+8°C	1800	1380/1430	700	50	413 / 10 x ¼	R134a	215	277	€ 3.050
							R290	218	280	€ 3.080

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient
- GN 1/4 baskets range for top unit

Options

Options	Price (€)
GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	<p>Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 350</p>
	<p>Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system</p>	<p>€ 450</p>



SGR-135



SGR-180

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
SGR-135	-2°C+8°C	1350	1110/1150	700	50	264 / 7 x ¼	R134a	215	277	€ 2.100
							R290	218	280	€ 2.130
SGR-180	-2°C+8°C	1800	1110/1150	700	50	413 / 10 x ¼	R134a	215	277	€ 2.350
							R290	218	280	€ 2.380

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient
- GN 1/4 baskets range for top unit

Options

Price (€)

GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350
	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system	€ 450



PGR-135-MR
PGR-180-MR



PGR-135-GR
PGR-180-GR

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
PGR-135-MR	-2°C+8°C	1350	1380/1430	700	50	264 / 7 x ¼	R134a	215 + 149	277 + 140	€ 2.830
							R290	218 + 131	280 + 158	€ 2.890
PGR-180-MR	-2°C+8°C	1800	1380/1430	700	50	413 / 10 x ¼	R134a	215 + 149	277 + 140	€ 3.300
							R290	218 + 131	280 + 158	€ 3.360
PGR-135-GR	-2°C+8°C	1350	1380/1430	700	50	264 / 7 x ¼	R134a	215 + 149	277 + 140	€ 2.810
							R290	218 + 131	280 + 158	€ 2.870
PGR-180-GR	-2°C+8°C	1800	1380/1430	700	50	413 / 10 x ¼	R134a	215 + 149	277 + 140	€ 3.380
							R290	218 + 131	280 + 158	€ 3.440



* The Topping Units are included in price

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Stainless Steel worktop
- GN 1/1 Shelves made of plasticized steel wire, height adjustable
- Stainless Steel adjustable legs, from 100 to 150 mm
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A, R 404 A
- Operating temperature 38°C ambient
- GN 1/4 baskets range for top unit

Options

Options	Price (€)
GN 1/ 1 Extra shelf	20
GN 1/ 1 Slides extra set	15
Lock Kit	40
4 castors set	70
6 castors set	105
220 V 60Hz	40
Double drawers set	350
Triple drawers set	450
Short legs, from 70 to 90 mm	20
Long legs, from 130 to 190 mm	20

	Increase of price by changing door to double drawers set, detachable telescopic SS runners, soft-closing system	€ 350
	Increase of price by changing door to triple drawers set, detachable telescopic SS runners, soft-closing system	€ 450



TU-135
TU-150
TU-180
TU-200



TU-135-GL
TU-150-GL
TU-180-GL
TU-200-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Insulation Thickness (mm)	Net Capacity (L)	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
TU-135	-2°C+8°C	1350	260	336	50	5x1/4	R134a	149	140	€ 850
							R290	131	158	€ 880
TU-150	-2°C+8°C	1500	260	336	50	6x1/4	R134a	149	140	€ 900
							R290	131	158	€ 930
TU-180	-2°C+8°C	1800	260	336	50	8x1/4	R134a	149	140	€ 950
							R290	131	158	€ 980
TU-200	-2°C+8°C	2000	260	336	50	9x1/4	R134a	149	140	€ 1.000
							R290	131	158	€ 1.030
TU-135-GL	-2°C+8°C	1350	260	336	50	5x1/4	R134a	149	140	€ 900
							R290	131	158	€ 930
TU-150-GL	-2°C+8°C	1500	260	336	50	6x1/4	R134a	149	140	€ 950
							R290	131	158	€ 980
TU-180-GL	-2°C+8°C	1800	260	336	50	8x1/4	R134a	149	140	€ 1.000
							R290	131	158	€ 1.030
TU-200-GL	-2°C+8°C	2000	260	336	50	9x1/4	R134a	149	140	€ 1.050
							R290	131	158	€ 1.080

Description

- Stainless Steel exterior, bottom side galvanized panel
- Stainless Steel interior
- GN 1/4 containers capacity (Not included)
- Adjustable supports
- Cold plate evaporator
- Fan assisted condenser unit
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Operating temperature 38°C ambient

Options

Options	Price (€)
220 V 60Hz	40



BBC-60-SS



BBC-90-SS



BBC-135-SS

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Net Capacity (L)	Storage Capacity	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
BBC-60-SS	+4°C+8°C	600	900/910	535	150	144 x 33 cl (Ø60mm)	R134a	215	277	€ 1.070
							R290	218	280	€ 1.100
BBC-90-SS	+4°C+8°C	900	900/910	535	250	207 x 33 cl (Ø60mm)	R134a	215	277	€ 1.270
							R290	218	280	€ 1.300
BBC-135-SS	+4°C+8°C	1350	900/910	535	315	326 x 33 cl (Ø60mm)	R134a	300	350	€ 1.620
							R290	264	418	€ 1.650

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Shelves made of plasticized steel wire, height adjustable
- Adjustable supports
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A
- Operating temperature 38°C ambient
- Insulation thickness 30 mm

Options

Price (€)

Extra shelf / door	30
220 V 60Hz	40



BBC-60-SS-GL



BBC-90-SS-GL



BBC-135-SS-GL

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Net Capacity (L)	Storage Capacity	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
BBC-60-SS-GL	+4°C+8°C	600	900/910	535	150	144 x 33 cl (Ø60mm)	R134a	215	277	€ 1.170
							R290	218	280	€ 1.200
BBC-90-SS-GL	+4°C+8°C	900	900/910	535	250	207 x 33 cl (Ø60mm)	R134a	215	277	€ 1.430
							R290	218	280	€ 1.460
BBC-135-SS-GL	+4°C+8°C	1350	900/910	535	315	326 x 33 cl (Ø60mm)	R134a	300	350	€ 1.880
							R290	264	418	€ 1.910

Description

- Stainless Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Shelves made of plasticized steel wire, height adjustable
- Adjustable supports
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A
- Operating temperature 38°C ambient
- Insulation thickness 30 mm

Options

Price (€)

Extra shelf / door	30
220 V 60Hz	40



BBC-60



BBC-90



BBC-135

Model	Range	Length (mm)	Height (mm)	Depth (mm)	Net Capacity (L)	Storage Capacity	Coolant	Standard Power Consumption (W)	Refrigeration Power (W)	Price (€)
BBC-60	+4°C+8°C	600	900/910	535	150	144 x 33 cl (Ø60mm)	R134a	215	277	€ 1.000
							R290	218	280	€ 1.030
BBC-90	+4°C+8°C	900	900/910	535	250	207 x 33 cl (Ø60mm)	R134a	215	277	€ 1.200
							R290	218	280	€ 1.230
BBC-135	+4°C+8°C	1350	900/910	535	315	326 x 33 cl (Ø60mm)	R134a	300	350	€ 1.600
							R290	264	418	€ 1.630

Description

- Plastic Coated Steel exterior, rear side galvanized panel
- Stainless Steel interior
- Shelves made of plasticized steel wire, height adjustable
- Adjustable supports
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating.
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Digital temperature control, optimized defrost
- Cooling Gas CFC Free: R 134 A
- Operating temperature 38°C ambient
- Insulation thickness 30 mm

Options

Price (€)

Extra shelf / door	30
220 V 60Hz	40



GW-40

Model	Basket Size (mm)	Dimensions (mm)	Useful Height (mm)	Racks Per Hour	Washing Cycles (sec)	Washing Pump (W)	Boiler Heating Element (kW)	Tank Heating Element (kW)	Max. Input (kW)	Tank / Boiler Capacity (L)	Tank / Boiler Set Temp (°C)	Price (€)
GW-40	400 x 400	485 x 550 x 780	300	30 / 20	120 / 180	260	3	1,8	3,26	10,5 / 5,5	55 / 85	€ 1.450

Description

- Stainless Steel AISI 304 washing zone
- Glass Fiber reinforced PP plastic parts
- Door operated start and stop
- Removable washing and rinsing arms
- Removable washing and rinsing nozzles
- Water level safety
- Wash pump filter
- Water inlet hose
- Drainage Hose
- Lime resistant Incolay 800 heating elements
- Drainage Pump
- 230/1N/50 Hz
- 1 Flat Basket

Options

Options	Price (€)
Detergent Dispenser	120
Rinse Aid Dispenser	120
Extra Basket	25



UD-50

Model	Basket Size (mm)	Dimensions (mm)	Useful Height (mm)	Racks Per Hour	Washing Cycles (sec)	Washing Pump (W)	Boiler Heating Element (kW)	Tank Heating Element (kW)	Max. Input (kW)	Tank / Boiler Capacity (L)	Tank / Boiler Set Temp (°C)	Price (€)
UD-50	500 x 500	585 x 610 x 830	320	30 / 20	120 / 180	650	4,5	3	5,2	20 / 7	55 / 85	€ 1.500

Description

- Stainless Steel AISI 304 washing zone
- Glass Fiber reinforced PP plastic parts
- Door operated start and stop
- Removable washing and rinsing arms
- Removable washing and rinsing nozzles
- Water level safety
- Wash pump filter
- Water inlet hose
- Drainage Hose
- Lime resistant Incolay 800 heating elements
- Drainage Pump
- 230/1N/50 Hz
- 2 Baskets (one for dishes and one flat)

Options

Options	Price (€)
Detergent Dispenser	120
Rinse Aid Dispenser	120
Extra Basket	25



HD-50

Model	Basket Size (mm)	Dimensions (mm)	Useful Height (mm)	Racks Per Hour	Washing Cycles (sec)	Washing Pump (W)	Boiler Heating Element (kW)	Tank Heating Element (kW)	Max. Input (kW)	Tank / Boiler Capacity (L)	Tank / Boiler Set Temp (°C)	Price (€)
HD-50	500 x 500	670 x 730 x 1455 (max. 1805)	380	40 / 30	90 / 120	650	9	3	12,7	20 / 7	55 / 85	€ 2.200

Description

- Stainless Steel AISI 304 washing zone
- Glass Fiber reinforced PP plastic parts
- Door operated start and stop
- Removable washing and rinsing arms
- Removable washing and rinsing nozzles
- Water level safety
- Wash pump filter
- Water inlet hose
- Drainage Hose
- Lime resistant Incolay 800 heating elements
- 230/1N/50 Hz
- 2 Baskets (one for dishes and one flat)

Options

Options	Price (€)
Detergent Dispenser	120
Rinse Aid Dispenser	120
Drainage Pump	80
Extra Basket	25

A series of horizontal dashed lines for taking notes.

VODINOX®

REFRIGERATION AND DISHWASHING


www.vodinox.com

Deri O.S.B. Alsancak Sokak
No: 4/A 34956
Tuzla / İSTANBUL / TURKEY

Tel: +90 216 504 00 59


info@vodinox.com